

Safety Data Sheet

according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

1 Identification

1.1 Product identifier

Trade name: **Osmo TopOil**

Article number: 3056, 3025, 3026

Application of the substance / the mixture Paint
Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf

Information department: Product safety department
Phone: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

24h-Emergency Phone Number:
For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or Night within USA and Canada 1-800-424-9300
Outside USA and Canada 001-703-527-3887 (WISAG FMO cargo Services GmbH & Co.KG)

Importer Osmo Wood and Colour Canada Ltd.
5515 – 92 ST NW
Edmonton, Alberta T6E 3A4
Canada
Tel: 001 (877) 746 6583
E-mail: info@osmo.ca

2 Hazard identification

2.1 Classification of the substance or mixture

Classification according to Hazardous Products Regulations

Flam. Liq. 4 H227 Combustible liquid.

2.2 Label elements

Labelling according to Hazardous

Products Regulations The product is classified and labeled according to the CLP regulation.

Hazard pictograms Void

Signal word Warning

Hazard statements H227 Combustible liquid.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from flames and hot surfaces. – No smoking.
P262	Do not get in eyes, on skin, or on clothing.

(Contd. on page 2)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

Trade name: Osmo TopOil

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P403 Store in a well-ventilated place.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Observe the general safety regulations when handling chemicals.
 Always wear a dust mask when sanding.

Hazard description:**WHMIS-symbols:**

B3 - Combustible liquid

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 0
 Fire = 2
 Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 0
 Fire = 2
 Reactivity = 0

2.3 Other hazards

Do not eat or drink while working.
 Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

3 Composition/Information on ingredients

3.2 Mixtures**Description:**

Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-48-9	aliphatic hydrocarbons, C10-C13	 Asp. Tox. 1, H304; Flam. Liq. 4, H227	30-60%
------------	---------------------------------	---	--------

4 First aid measures

4.1 Description of first aid measures**General information:**

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety Data Sheet
according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

Trade name: Osmo TopOil

(Contd. of page 2)

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters
Protective equipment: Mouth respiratory protective device.
Additional information Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
Keep away from ignition sources

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up: Warm water and cleansing agent
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Keep receptacles tightly sealed.
Prevent formation of aerosols.

(Contd. on page 4)

Safety Data Sheet
 according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

Trade name: Osmo TopOil

(Contd. of page 3)

Information about protection**against explosions and fires:** Keep ignition sources away - Do not smoke.**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by****storerooms and receptacles:** Store only in the original receptacle.
Store in a cool location.**Information about storage in one****common storage facility:** Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.**Further information about****storage conditions:** Store in cool, dry conditions in well sealed receptacles.
Keep receptacle tightly sealed.**Storage class:** 10**7.3 Specific end use(s)** No further relevant information available.**8 Exposure controls/ Personal protection****Additional information about****design of technical systems:** No further data; see item 7.**8.1 Control parameters****Components with limit values that****require monitoring at the****workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists that were valid during the creation were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic****measures:**Immediately remove all soiled and contaminated clothing.
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.**Breathing equipment:**Not necessary if room is well-ventilated.
Use suitable respiratory protective device only when aerosol or mist is formed.
Short term filter device:

Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 °C)).

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

To avoid skin problems reduce the wearing of gloves to the required minimum.

(Contd. on page 5)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

Trade name: Osmo TopOil

(Contd. of page 4)

Material of gloves	Nitrile rubber, NBR
Penetration time of glove material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the permanent contact gloves made of the following materials are suitable:	Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).
For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:	Nitrile rubber, NBR
As protection from splashes gloves made of the following materials are suitable:	Recommended thickness of the material: ≥ 0.1 mm
Eye protection:	Goggles recommended during refilling.
Body protection:	Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Viscous
Color:	Colorless
Odor:	Mild
Odor threshold:	Not determined.

pH-value: Not applicable

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 180 °C (DIN 51751)

Flash point: > 61 °C (DIN EN ISO 2719)

Ignition temperature: 240 °C

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 6)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

Trade name: Osmo TopOil

(Contd. of page 5)

Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Vapor pressure:	Typical 30 - 93 Pa (0 °C / 32 °F) (solvent)
Density at 20 °C:	0.93-0.94 g/cm ³ (DIN 51757)
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water): Data not available	
Viscosity:	
Dynamic at 20 °C:	60-65 s (DIN 53211/4mm)
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

10 Stability and reactivity

10.1 Reactivity	No further relevant information available.
10.2 Chemical stability	
Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition products:	Carbon monoxide and carbon dioxide Nitrogen oxides (NO _x)
Additional information:	Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
------	------	-------------------------------

(Contd. on page 7)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

Trade name: Osmo TopOil

(Contd. of page 6)

Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye: not tested

Sensitization: Based on available data, the classification criteria are not met.

Additional toxicological information:**Carcinogenic categories**

IARC (International Agency for Research on Cancer)		
7631-86-9	silicon dioxide, chemically prepared	3
14808-60-7	Quartz (SiO ₂)	1
NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K

12 Ecological information

12.1 Toxicity**Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

13.1 Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Safety Data Sheet
according to HPR, Schedule 1

Printing date 08/28/2017

Reviewed on 08/28/2017

Trade name: Osmo TopOil**Recommended cleansing agent:** Solvent naphtha

(Contd. of page 7)

14 Transport information**14.1 UN-Number**

DOT, TDG, ADN, IMDG, IATA Void

14.2 UN proper shipping name

DOT, TDG, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)DOT, TDG, ADN, IMDG, IATA
Class Void**14.4 Packing group**

DOT, TDG, IMDG, IATA Void

14.5 Environmental hazards:**Marine pollutant:** No**14.6 Special precautions for user**

Not applicable.

**14.7 Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code**

Not applicable.

UN "Model Regulation":

Void

15 Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Sara****Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

7727-43-7 | barium sulphate, natural

112-34-5 | 2-(2-butoxyethoxy)ethanol

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Canadian substance listings:**Canadian Domestic Substances List (DSL)**

All ingredients are listed.

(Contd. on page 9)

