

Safety Data Sheet

E497 Thermoset Mold Release™

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Thermoset Mold Release™
Product Code: E497
Product Use: Mold Release
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard
Symbols



GHS Classification

Flammable Aerosol Category 1
Gases under pressure - Liquefied Gas
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word

Danger

Hazard Statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Call a POISON CENTER or doctor/physician if you feel unwell.
Specific treatment (see ... on this label).
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent
Hydrocarbon propellant	68476-86-8	
Petroleum distillates	8052-41-3	60 - 80
Ether propellant	115-10-6	1-20
Hydrocarbon propellant	68476-86-8	1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 1	Flammability: 4	Physical: 1	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.

Ingestion: Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions.

Fire Fighting Instructions: Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Place waste material into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor. This material can be harmful or irritating. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Do not store at temperatures above 120 degrees F. Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the MSDS (from known, suspected or apparent adverse effects). Ventilation is required to maintain operator exposure below published exposure limits.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Hydrocarbon propellant	68476-86-8	Not established	Not established	Not established
Petroleum distillates	8052-41-3	100 ppm TWA	500 ppm	Not established
Ether propellant	115-10-6	Not established	Not established	Not established
Hydrocarbon propellant	68476-86-8	1000ppm	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	White to off-white	Upper Flammability Limit (%):	Not applicable
Odor:	Petroleum solvent	Vapor Pressure (PSIG @ 70°F):	46.0
Odor Threshold:	Mild	Vapor Density [air = 1]:	3.91
pH:	Not applicable	Relative Density (H2O=1):	0.73
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	Not applicable
Evaporation Rate:	0.1-0.5 (n-Butyl acetate = 1)	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	80 - 100		

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides. Powdered metals.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. If heated with peroxides present, violent decomposition can occur.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity: No data available.

Ingredient	CAS #	Toxicological Data
Petroleum distillates	8052-41-3	Dermal LD50 Rabbit > 3 g/kg Oral LD50 Rat > 5 g/kg
Ether propellant	115-10-6	Inhalation LC50 Rat = 164000 ppm
Hydrocarbon propellant	68476-86-8	No data available Inhalation LC50 (4h) Rat 658 mg/L

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available
Mobility: No data available

Ingredient	CAS #	Toxicological Data
Ether propellant	115-10-6	48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

16. OTHER INFORMATION

Other Information : MSDS Prepared by L. Dean Swartz, MSDS Coordinator

Version Date: 06/07/15

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.