Memory Pendant



Needed:

Mandrel A, drill 7mm, bushing 1A

Preparing the blank


- 1. Cut the blank ¼" longer than the brass tube so you can square it off once the tube has been glued in.
- **2.** Drill through the center lengthwise with 7 mm drill.
- **3.** Scuff up the tube with sandpaper to clean off the oxidation and give the glue a better adhesion surface.
- 4. Plug the tube ends with a material of your choice we recommend baseplate wax to keep the glue from getting into the tube. Just push the ends of the tube into a thin section of the material to form a plug.
- 5. Roll the tube in the glue and insert it into the blank with a twisting motion until it is equidistant between both



ends of the blank.

- **6.** Set aside until the glue has had time to reach its maximum strength.
- **7.** When the glue has cured, use a hobby knife to remove the plugs from the ends.
- 8. Square off the ends of the blank until you can see bright brass tube. STOP at this point. This can be done with the proper jig and a disk sander.

Turning the blank



- **1.** Assemble the blank and bushings on the mandrel.
- 2. Tighten the tailstock and lightly tighten the nut that holds the blank. Over-tightening can bend your mandrel and cause your kit to come out oval. You may use a spacer to give you more room between the thumbnut and the last bushing.
- **3.** Turn the blank to the desired contour, using the bushings as a sizing guide.

- **4.** Sand the surface in progressive steps until you get to 400 or 600 grit.
- **5.** For a high polish finish, continue sanding with micro mesh to 12,000 grit.
- **6.** Apply finish of your choice and polish. Remove blank from the mandrel.

Assembling the kit

- 1. Press the threaded insert into the bottom of the tube until flush with the barrel.
- 2. Screw on the bottom finial.
- **3.** Press the top finial into the top of the barrel.

