Heirloom Coffee Scoop

Needed:

3/8" threaded mandrel 16tpi (BSMAND-38-16)

11/32" drill bit

3/8" x 16tpi tap

Live Centre

Please note: you will need a Jacobs chuck or drill chuck for your lathe to make this kit.

Preparing and turning the blank

- **1.** Select a turning blank at least 1" square x 5.5" long. Square the end of the drill end of the blank.
- 2. Mark a centre mark on the end of the blank and using a 11/32" drill, drill a hole 1-1/4" deep.
- **3.** Using a 3/8"x 16tpi drill tap, slowly and carefully tap the hole in the blank.
- **4.** Screw the threaded end of the mandrel into this hole until the blank shoulders against the round stop collar.
- **5.** Mount the shaft of the mandrel onto your lathe using a Jacobs chuck or drill chuck. Support the other end of the blank with your live tailstock centre.



- **6.** Turn the blank to the desired shape, leaving ½" of waste material on the tailstock end. Sand and finish the handle blank.
- **7.** Trim off the ½" waste piece on the lathe. Sand and finish the end.

Assembling the parts

- **1.** Unscrew the mandrel from the turned blank and set aside.
- **2.** Unscrew the threaded insert from the coffee scoop. Glue the threaded insert into the handle by placing a small amount of glue into the hole and threading the long end of the insert into the handle.
- **3.** Once the glue has cured, thread the coffee scoop onto the handle.



