

2-piece bushing set EVER-PCL-BU

• 3/8" Drill Bit

Glue (Thick CA or Epoxy)



PREPARING THE BLANK:

- Cut one blank to the length of the brass tube (add 1/16" to each end for squaring off).
- Drill a 3/8" center hole lengthwise through the blank.
- Spread the glue over the tube. Insert the tube into the blank with a twisting motion to spread the glue evenly inside. Center the tube lengthwise in the blank.
- When the glue dries, square the ends of the blank. Use a barrel trimmer, pen blank squaring jig, or a belt/disc sander to square the end. Take the wood down flush to the brass tube.



TURNING THE BLANK:

- Mount the bushings and blanks according the diagram above.
- Thread on the knurled nut and hand tighten to hold all components in place.
- Slide the tailstock up snugly against the mandrel shaft inserting the live center point into the mandrel dimple, lock in place.
- Hand tighten the quill adjustment to firm up the mandrel. (DO NOT overtighten, it could damage the mandrel.
- Using sharp tools, turn the blank down close to the bushing diameter. Turn the barrel (straight or to a profile of your choice)
- Sand the blank down to be flush with the bushings gradually increasing the sandpaper grits.
- Finish the barrel with your choice of polish. Allow sufficient time for the polish to cure.

Diagram A



ASSEMBLY

- · Layout Finished parts according to Diagram A.
- Slide the pen clip onto the bottom of the cap, then press them into one end of the tube.
- Insert the eraser into the top of the cap.
- Insert the tip holder to the other end of the tube.
- When not in use, reverse the tip holder assembly to protect the pencil tip.
- You can unscrew the pencil tip to replace it with a new tip.